


Item description/product images



Minimum bend radius:



Description

Material:

Edge protection EPDM or PVC. Seal EPDM foam rubber.

Version:

Black.

Note:

In addition to edge protection, these profiles also provide a sealing function against moisture, dust and dirt for other elements such as doors, hatches or housing covers. Depending on the shape of the foam rubber profile, they can be used in a wide range of applications.

We recommend compressing the sealing lip of the edge protection by max.50%. To ensure the best possible seal, the lips should be compressed by 30-40%. These specifications are recommendations; in practice, they are individually dependent on the application and the parts used.

UL50, UL50E and UL94HB certified.

Assembly:

Easy, quick and smooth assembly. The edge protection profile is easy to push on by hand and remains in place. No adhesive or fastening material required.


On request:


Other lengths.

© norelem www.norelem.com



Drawings





Overview of items

Order No.	Form	Main material	L	Clamping range mm	Minimum bend radius mm	В	Н
96521-015X2000	Α	EPDM	2000	0,5-1,5	A=50 B=180 C=25 D=25	8	15
96521-015X5000	Α	EPDM	5000	0,5-1,5	A=50 B=180 C=25 D=25	8	15
96521-015X10000	Α	EPDM	10000	0,5-1,5	A=50 B=180 C=25 D=25	8	15
96521-015X20000	Α	EPDM	20000	0,5-1,5	A=50 B=180 C=25 D=25	8	15
96521-015X50000	Α	EPDM	50000	0,5-1,5	A=50 B=180 C=25 D=25	8	15