

## Item description/product images

**Description****Product description:**

These tubular handles impresses with a combination of solid appearance, high stability and extreme lightness. The patented fastening system enables the handles to be installed from the rear with no screws visible from the front. With its easy-to-clean and abrasion-resistant surface, the handle also blends in perfectly with its surroundings.

**Material:**

Round tube aluminium EN AW-6060.  
steel tapped bush.

**Version:**

Anodised natural tone or powder-coated black, ruby red RAL 3003 or traffic red RAL 3020.

**Note:**

Fastening materials are not supplied. Cap screws with thread lock are recommended for a secure and long-lasting attachment.

**Assembly:**

The tubular handle can be mounted from the rear. DIN socket head screws or hexagon head bolts with thread size M8 are provided for this purpose.

**Advantages:**

Solid appearance combined with low weight

Timeless elegant design.

Ergonomic handle shape.

Patented fastening system for rear mounting.


**Accessory:**

07160 Socket head screws DIN 912 / DIN EN ISO 4762 with thread lock

07160 Socket head screws DIN 912 / DIN EN ISO 4762

07171 Hex head screws DIN 933 / DIN-EN-ISO 4017

## Drawings



## Overview of items

## Tubular handles round, aluminium

| Order No.        | Main colour           | Surface finish body | A   | B  | D  | H  | L     | Load capacity N |
|------------------|-----------------------|---------------------|-----|----|----|----|-------|-----------------|
| 06938-01-250083  | Adapter plate         | for handwheels      | 250 | 30 | M8 | 65 | 296,4 | 1000            |
| 06938-01-300083  | Adapter plate         | for handwheels      | 300 | 30 | M8 | 65 | 346,4 | 1000            |
| 06938-01-400083  | Adapter plate         | for handwheels      | 400 | 30 | M8 | 65 | 446,4 | 1000            |
| 06938-01-500083  | Adapter plate         | for handwheels      | 500 | 30 | M8 | 65 | 546,4 | 1000            |
| 06938-01-250081  | 9 hours               | keyboard tray       | 250 | 30 | M8 | 65 | 296,4 | 1000            |
| 06938-01-300081  | 9 hours               | keyboard tray       | 300 | 30 | M8 | 65 | 346,4 | 1000            |
| 06938-01-400081  | 9 hours               | keyboard tray       | 400 | 30 | M8 | 65 | 446,4 | 1000            |
| 06938-01-500081  | 9 hours               | keyboard tray       | 500 | 30 | M8 | 65 | 546,4 | 1000            |
| 06938-01-2500827 | Adapter plate         | keyboard tray       | 250 | 30 | M8 | 65 | 296,4 | 1000            |
| 06938-01-3000827 | Adapter plate         | keyboard tray       | 300 | 30 | M8 | 65 | 346,4 | 1000            |
| 06938-01-4000827 | Adapter plate         | keyboard tray       | 400 | 30 | M8 | 65 | 446,4 | 1000            |
| 06938-01-5000827 | Adapter plate         | keyboard tray       | 500 | 30 | M8 | 65 | 546,4 | 1000            |
| 06938-01-2500884 | 750X50000 (+/- 10 mm) | keyboard tray       | 250 | 30 | M8 | 65 | 296,4 | 1000            |
| 06938-01-3000884 | 750X50000 (+/- 10 mm) | keyboard tray       | 300 | 30 | M8 | 65 | 346,4 | 1000            |
| 06938-01-4000884 | 750X50000 (+/- 10 mm) | keyboard tray       | 400 | 30 | M8 | 65 | 446,4 | 1000            |
| 06938-01-5000884 | 750X50000 (+/- 10 mm) | keyboard tray       | 500 | 30 | M8 | 65 | 546,4 | 1000            |