



## Safety Data Sheet according to (EC) No 1907/2006 as amended

Page 1 of 18

LOCTITE SF 7471

SDS No. : 153556  
V004.1

Revision: 16.02.2024

printing date: 10.10.2024

Replaces version from: 20.06.2022

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

LOCTITE SF 7471

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:

Activator

#### 1.3. Details of the supplier of the safety data sheet

Henkel AG & Co. KGaA

Henkelstr. 67

40589 Düsseldorf

Germany

Phone: +49 211 797 0

For Safety Data Sheet updates please visit our website <https://mysds.henkel.com/index.html#/appSelection> or [www.henkel-adhesives.com](http://www.henkel-adhesives.com).

#### 1.4. Emergency telephone number

The Henkel information service also provides an around-the-clock telephone service on phone no.+49-(0)211-797-3350 for exceptional cases.

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification (CLP):

Flammable liquids	Category 2
H225 Highly flammable liquid and vapour.	
Serious eye irritation	Category 2
H319 Causes serious eye irritation.	
Skin sensitizer	Category 1
H317 May cause an allergic skin reaction.	
Specific target organ toxicity - single exposure	Category 3
H336 May cause drowsiness or dizziness.	
Target organ: Central nervous system	
Chronic hazards to the aquatic environment	Category 3
H412 Harmful to aquatic life with long lasting effects.	

#### 2.2. Label elements

##### Label elements (CLP):

**Hazard pictogram:**



**Contains**

acetone

Diethylol-p-toluidine  
benzothiazole-2-thiol

**Signal word:**

Danger

**Hazard statement:**

H225 Highly flammable liquid and vapour.  
H317 May cause an allergic skin reaction.  
H319 Causes serious eye irritation.  
H336 May cause drowsiness or dizziness.  
H412 Harmful to aquatic life with long lasting effects.

**Supplemental information**

EUH066 Repeated exposure may cause skin dryness or cracking.

**Precautionary statement:**

\*\*\*\* For consumer use only: P101 If medical advice is needed, have product container or label at hand. P102 Keep out of reach of children. P501 Dispose of contents/container in accordance with national regulation.\*\*\*

**Precautionary statement:  
Prevention**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P261 Avoid breathing vapors.  
P273 Avoid release to the environment.  
P280 Wear protective gloves/protective clothing.

**Precautionary statement:  
Response**

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.  
P337+P313 If eye irritation persists: Get medical advice/attention.

**Precautionary statement:  
Storage**

P403+P235 Store in a well-ventilated place. Keep cool.

**2.3. Other hazards**

None if used properly.  
Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

**Following substances are present in a concentration  $\geq$  the concentration limit for depiction in Section 3 and fulfill the criteria for PBT/vPvB, or were identified as endocrine disruptor (ED):**

This mixture does not contain any substances in a concentration  $\geq$  the concentration limit for depiction in Section 3 that are assessed to be a PBT, vPvB or ED.

**SECTION 3: Composition/information on ingredients**

**3.2. Mixtures**

**Declaration of the ingredients according to CLP (EC) No 1272/2008:**

<b>Hazardous components CAS-No. EC Number REACH-Reg No.</b>	<b>Concentration</b>	<b>Classification</b>	<b>Specific Conc. Limits, M-factors and ATEs</b>	<b>Add. Information</b>
acetone 67-64-1 200-662-2 01-2119471330-49	50- 100 %	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336		EU OEL EUEXPL2D
Propan-2-ol 67-63-0 200-661-7 01-2119457558-25	10- 20 %	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336		
Diethylol-p-toluidine 3077-12-1 221-359-1 01-2120791684-40	1- < 3 %	Skin Sens. 1, H317 Acute Tox. 4, Oral, H302 Eye Dam. 1, H318 Aquatic Chronic 3, H412		
benzothiazole-2-thiol 149-30-4 205-736-8 01-2119485805-26	0,1- < 1 %	Skin Sens. 1, H317 Aquatic Chronic 1, H410 Aquatic Acute 1, H400	M acute = 1 M chronic = 1	

**If no ATE values are displayed, please refer to LD/LC50 values in Section 11.  
For full text of the H - statements and other abbreviations see section 16 "Other information".**

**SECTION 4: First aid measures**

**4.1. Description of first aid measures**

Inhalation:

Move to fresh air. If symptoms persist, seek medical advice.

Skin contact:

Rinse with running water and soap.

Obtain medical attention if irritation persists.

Eye contact:

Rinse immediately with plenty of running water (for 10 minutes), seek medical attention from a specialist.

Ingestion:

Rinse out mouth, drink 1-2 glasses of water, do not induce vomiting.

Seek medical advice.

**4.2. Most important symptoms and effects, both acute and delayed**

EYE: Irritation, conjunctivitis.

Vapors may cause drowsiness and dizziness.

SKIN: Rash, Urticaria.

**4.3. Indication of any immediate medical attention and special treatment needed**

See section: Description of first aid measures

**SECTION 5: Firefighting measures**

**5.1. Extinguishing media**

**Suitable extinguishing media:**

Carbon dioxide, foam, powder

**Extinguishing media which must not be used for safety reasons:**

None known

**5.2. Special hazards arising from the substance or mixture**

In the event of a fire, carbon monoxide (CO), carbon dioxide (CO<sub>2</sub>) and nitrogen oxides (NO<sub>x</sub>) can be released.

**5.3. Advice for firefighters**

Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

**Additional information:**

In case of fire, keep containers cool with water spray.

## SECTION 6: Accidental release measures

**6.1. Personal precautions, protective equipment and emergency procedures**

Avoid contact with skin and eyes.

Ensure adequate ventilation.

Wear protective equipment.

**6.2. Environmental precautions**

Do not empty into drains / surface water / ground water.

**6.3. Methods and material for containment and cleaning up**

Dispose of contaminated material as waste according to Section 13.

For small spills wipe up with paper towel and place in container for disposal.

For large spills absorb onto inert absorbent material and place in sealed container for disposal.

**6.4. Reference to other sections**

See advice in section 8

## SECTION 7: Handling and storage

**7.1. Precautions for safe handling**

Avoid skin and eye contact.

See advice in section 8

Use only in well-ventilated areas.

Vapours should be extracted to avoid inhalation.

Keep away from sources of ignition - no smoking.

**Hygiene measures:**

Wash hands before work breaks and after finishing work.

Do not eat, drink or smoke while working.

Good industrial hygiene practices should be observed.

**7.2. Conditions for safe storage, including any incompatibilities**

Ensure good ventilation/extraction.

Refer to Technical Data Sheet.

**7.3. Specific end use(s)**

Activator

**SECTION 8: Exposure controls/personal protection**

**8.1. Control parameters**

**Occupational Exposure Limits**

Valid for  
Germany

Ingredient [Regulated substance]	ppm	mg/m <sup>3</sup>	Value type	Short term exposure limit category / Remarks	Regulatory list
Acetone 67-64-1 [ACETONE]	500	1.210	Time Weighted Average (TWA):	Indicative	ECLTV
Acetone 67-64-1	500	1.200	Exposure limit(s):	2 If the AGW and BGW values are complied with, there should be no risk of reproductive damage (see Number 2.7).	TRGS 900
Acetone 67-64-1			Short Term Exposure Classification:	Category I: substances for which the localized effect has an assigned OEL or for substances with a sensitizing effect in respiratory passages.	TRGS 900
Propan-2-ol 67-63-0			Short Term Exposure Classification:	Category II: substances with a resorptive effect.	TRGS 900
Propan-2-ol 67-63-0	200	500	Exposure limit(s):	2 If the AGW and BGW values are complied with, there should be no risk of reproductive damage (see Number 2.7).	TRGS 900
Benzothiazole-2-thiol 149-30-4		4	Exposure limit(s):	If the AGW and BGW values are complied with, there should be no risk of reproductive damage (see Number 2.7).	TRGS 900

**Predicted No-Effect Concentration (PNEC):**

Name on list	Environmental Compartment	Exposure period	Value				Remarks
			mg/l	ppm	mg/kg	others	
acetone 67-64-1	aqua (intermittent releases)		21 mg/l				
acetone 67-64-1	sewage treatment plant (STP)		100 mg/l				
acetone 67-64-1	sediment (freshwater)				30,4 mg/kg		
acetone 67-64-1	sediment (marine water)				3,04 mg/kg		
acetone 67-64-1	Soil				29,5 mg/kg		
acetone 67-64-1	aqua (freshwater)		10,6 mg/l				
acetone 67-64-1	aqua (marine water)		1,06 mg/l				
Propan-2-ol 67-63-0	aqua (freshwater)		140,9 mg/l				
Propan-2-ol 67-63-0	aqua (marine water)		140,9 mg/l				
Propan-2-ol 67-63-0	sediment (freshwater)				552 mg/kg		
Propan-2-ol 67-63-0	sediment (marine water)				552 mg/kg		
Propan-2-ol 67-63-0	Soil				28 mg/kg		
Propan-2-ol 67-63-0	aqua (intermittent releases)		140,9 mg/l				
Propan-2-ol 67-63-0	sewage treatment plant (STP)		2251 mg/l				
Propan-2-ol 67-63-0	oral				160 mg/kg		
2,2'-[(4-Methylphenyl)imino]bisethanol 3077-12-1	aqua (freshwater)		0,026 mg/l				
2,2'-[(4-Methylphenyl)imino]bisethanol 3077-12-1	aqua (intermittent releases)		0,26 mg/l				
2,2'-[(4-Methylphenyl)imino]bisethanol 3077-12-1	aqua (marine water)		0,003 mg/l				
2,2'-[(4-Methylphenyl)imino]bisethanol 3077-12-1	sediment (freshwater)				0,121 mg/kg		
2,2'-[(4-Methylphenyl)imino]bisethanol 3077-12-1	sediment (marine water)				0,012 mg/kg		
2,2'-[(4-Methylphenyl)imino]bisethanol 3077-12-1	Sewage treatment plant		10 mg/l				
2,2'-[(4-Methylphenyl)imino]bisethanol 3077-12-1	Soil				0,009 mg/kg		
Benzothiazole-2-thiol 149-30-4	aqua (freshwater)		0,004 mg/l				
Benzothiazole-2-thiol 149-30-4	Freshwater - intermittent		0,005 mg/l				
Benzothiazole-2-thiol 149-30-4	aqua (marine water)		0 mg/l				
Benzothiazole-2-thiol 149-30-4	sewage treatment plant (STP)		0,3 mg/l				
Benzothiazole-2-thiol 149-30-4	sediment (freshwater)				0,147 mg/kg		
Benzothiazole-2-thiol 149-30-4	sediment (marine water)				0,015 mg/kg		
Benzothiazole-2-thiol 149-30-4	Soil				0,027 mg/kg		

**Derived No-Effect Level (DNEL):**

Name on list	Application Area	Route of Exposure	Health Effect	Exposure Time	Value	Remarks
acetone 67-64-1	Workers	Inhalation	Acute/short term exposure - local effects		2420 mg/m <sup>3</sup>	
acetone 67-64-1	Workers	dermal	Long term exposure - systemic effects		186 mg/kg	
acetone 67-64-1	Workers	Inhalation	Long term exposure - systemic effects		1210 mg/m <sup>3</sup>	
acetone 67-64-1	General population	dermal	Long term exposure - systemic effects		62 mg/kg	
acetone 67-64-1	General population	Inhalation	Long term exposure - systemic effects		200 mg/m <sup>3</sup>	
acetone 67-64-1	General population	oral	Long term exposure - systemic effects		62 mg/kg	
Propan-2-ol 67-63-0	Workers	dermal	Long term exposure - systemic effects		888 mg/kg	
Propan-2-ol 67-63-0	Workers	inhalation	Long term exposure - systemic effects		500 mg/m <sup>3</sup>	
Propan-2-ol 67-63-0	General population	dermal	Long term exposure - systemic effects		319 mg/kg	
Propan-2-ol 67-63-0	General population	inhalation	Long term exposure - systemic effects		89 mg/m <sup>3</sup>	
Propan-2-ol 67-63-0	General population	oral	Long term exposure - systemic effects		26 mg/kg	
2,2'-[(4-Methylphenyl)imino]bisethanol 3077-12-1	Workers	inhalation	Long term exposure - systemic effects		3,29 mg/m <sup>3</sup>	
2,2'-[(4-Methylphenyl)imino]bisethanol 3077-12-1	Workers	dermal	Long term exposure - systemic effects		0,47 mg/kg	
2,2'-[(4-Methylphenyl)imino]bisethanol 3077-12-1	General population	inhalation	Long term exposure - systemic effects		0,58 mg/m <sup>3</sup>	
2,2'-[(4-Methylphenyl)imino]bisethanol 3077-12-1	General population	dermal	Long term exposure - systemic effects		0,17 mg/kg	
2,2'-[(4-Methylphenyl)imino]bisethanol 3077-12-1	General population	oral	Long term exposure - systemic effects		0,16 mg/kg	
Benzothiazole-2-thiol 149-30-4	Workers	inhalation	Acute/short term exposure - systemic effects		70,4 mg/m <sup>3</sup>	
Benzothiazole-2-thiol 149-30-4	Workers	inhalation	Long term exposure - systemic effects		8,8 mg/m <sup>3</sup>	
Benzothiazole-2-thiol 149-30-4	Workers	dermal	Long term exposure - systemic effects		5 mg/kg	
Benzothiazole-2-thiol 149-30-4	Workers	dermal	Acute/short term exposure - systemic effects		40 mg/kg	
Benzothiazole-2-thiol 149-30-4	General population	oral	Acute/short term exposure - systemic effects		10 mg/kg	
Benzothiazole-2-thiol 149-30-4	General population	oral	Long term exposure - systemic effects		1,25 mg/kg	
Benzothiazole-2-thiol 149-30-4	General population	inhalation	Acute/short term exposure -		17,6 mg/m <sup>3</sup>	

			systemic effects			
Benzothiazole-2-thiol 149-30-4	General population	inhalation	Long term exposure - systemic effects		2,2 mg/m <sup>3</sup>	
Benzothiazole-2-thiol 149-30-4	General population	dermal	Acute/short term exposure - systemic effects		20 mg/kg	
Benzothiazole-2-thiol 149-30-4	General population	dermal	Long term exposure - systemic effects		2,5 mg/kg	

**Biological Exposure Indices:**

Ingredient [Regulated substance]	Parameters	Biological specimen	Sampling time	Conc.	Basis of biol. exposure index	Remark	Additional Information
Acetone 67-64-1 [Acetone]	acetone	Urine	Sampling time: End of shift.	50 mg/l	DE BGW		
Propan-2-ol 67-63-0	acetone	Blood	Sampling time: End of shift.	25 mg/l	DE BGW		
Propan-2-ol 67-63-0 [2-PROPANOL]	acetone	Urine	Sampling time: End of shift.	25 mg/l	DE BGW		

**8.2. Exposure controls:**

## Engineering controls:

Ensure good ventilation/extraction.

## Respiratory protection:

Ensure adequate ventilation.

An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area

Filter type: A (EN 14387)

## Hand protection:

Chemical-resistant protective gloves (EN 374).

Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):

nitrile rubber (NBR;  $\geq$  0.4 mm thickness)

Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):

nitrile rubber (NBR;  $\geq$  0.4 mm thickness)

This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

## Eye protection:

Wear protective glasses.

Protective eye equipment should conform to EN166.

## Skin protection:

Wear suitable protective clothing.

Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

## Advices to personal protection equipment:

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions. Personal protective equipment should conform to the relevant EN standard.



## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Delivery form	liquid
Colour	Amber to yellowish
Odor	Acetone
Physical state	liquid
Melting point	Not applicable, Product is a liquid
Solidification temperature	-95 °C (-139 °F)
Initial boiling point	56 °C (132.8 °F)no method / method unknown
Flammability	Flammable liquid
Explosive limits	
lower	2,6 % (V);
upper	12,8 % (V);
Flash point	-8 °C (17.6 °F) Estimated
Auto-ignition temperature	465 °C (869 °F)
Decomposition temperature	Not applicable, Substance/mixture is not self-reactive, no organic peroxide and does not decompose under foreseen conditions of use
pH	5 - 6
(20 °C (68 °F); Conc.: 100 % product)	
Viscosity (kinematic)	2,5 mm <sup>2</sup> /s
(25 °C (77 °F); )	
Viscosity (kinematic)	> 20,5 mm <sup>2</sup> /s
(40 °C (104 °F); )	
Solubility (qualitative)	Miscible
(20 °C (68 °F); Solvent: Water)	
Partition coefficient: n-octanol/water	Not applicable
Vapour pressure	Mixture
(20 °C (68 °F))	172 mm hg
Density	0,795 g/cm <sup>3</sup> no method / method unknown
(20 °C (68 °F))	
Relative vapour density:	2
(20 °C)	
Particle characteristics	Not applicable
	Product is a liquid

### 9.2. Other information

Other information not applicable for this product

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Reacts with strong oxidants.  
Reaction with strong acids.

### 10.2. Chemical stability

Stable under recommended storage conditions.

### 10.3. Possibility of hazardous reactions

See section reactivity

### 10.4. Conditions to avoid

Stable under normal conditions of storage and use.

### 10.5. Incompatible materials

See section reactivity.

### 10.6. Hazardous decomposition products

Irritating organic vapours.

**SECTION 11: Toxicological information****11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008****Acute oral toxicity:**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
acetone 67-64-1	LD50	5.800 mg/kg	rat	not specified
Propan-2-ol 67-63-0	LD50	5.840 mg/kg	rat	equivalent or similar to OECD Guideline 401 (Acute Oral Toxicity)
Diethylol-p-toluidine 3077-12-1	LD50	959 mg/kg	rat	equivalent or similar to OECD Guideline 401 (Acute Oral Toxicity)
benzothiazole-2-thiol 149-30-4	LD50	2.830 mg/kg	rat	not specified

**Acute dermal toxicity:**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
acetone 67-64-1	LD50	> 15.688 mg/kg	rabbit	Draize Test
Propan-2-ol 67-63-0	LD50	12.870 mg/kg	rabbit	OECD Guideline 402 (Acute Dermal Toxicity)
Diethylol-p-toluidine 3077-12-1	LD50	> 2.000 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)
benzothiazole-2-thiol 149-30-4	LD50	> 7.940 mg/kg	rabbit	not specified

**Acute inhalative toxicity:**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Test atmosphere	Exposure time	Species	Method
acetone 67-64-1	LC50	76 mg/l	vapour	4 h	rat	not specified
benzothiazole-2-thiol 149-30-4	LC50	> 1.270 mg/l	dust/mist	4 h	rat	not specified

**Skin corrosion/irritation:**

Solvent may remove essential oils from the skin making it susceptible to attack from other chemicals.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
acetone 67-64-1	not irritating		guinea pig	not specified
Propan-2-ol 67-63-0	slightly irritating	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
Diethylol-p-toluidine 3077-12-1	not irritating	24 h	rabbit	not specified

**Serious eye damage/irritation:**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
acetone 67-64-1	irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
Propan-2-ol 67-63-0	Category II		rabbit	equivalent or similar to OECD Guideline 405 (Acute Eye Irritation / Corrosion)
Diethylol-p-toluidine 3077-12-1	Category 1 (irreversible effects on the eye)		rabbit	equivalent or similar to OECD Guideline 405 (Acute Eye Irritation / Corrosion)

**Respiratory or skin sensitization:**

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Test type	Species	Method
acetone 67-64-1	not sensitising	Guinea pig maximisation test	guinea pig	not specified
Propan-2-ol 67-63-0	not sensitising	Buehler test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
Diethylol-p-toluidine 3077-12-1	sensitising	Mouse local lymphnode assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
benzothiazole-2-thiol 149-30-4	sensitising	Buehler test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
benzothiazole-2-thiol 149-30-4	sensitising	Guinea pig maximisation test	guinea pig	OECD Guideline 406 (Skin Sensitisation)

**Germ cell mutagenicity:**

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
acetone 67-64-1	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
acetone 67-64-1	negative	in vitro mammalian chromosome aberration test	with and without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
acetone 67-64-1	negative	mammalian cell gene mutation assay	without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Propan-2-ol 67-63-0	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		equivalent or similar to OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Propan-2-ol 67-63-0	negative	mammalian cell gene mutation assay	with and without		equivalent or similar to OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)

**Carcinogenicity**

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Sex	Method
acetone 67-64-1	not carcinogenic	dermal	424 d 3 times per week	mouse	female	not specified
Propan-2-ol 67-63-0		inhalation: vapour	104 w 6 h/d, 5 d/w	rat	male/female	OECD Guideline 451 (Carcinogenicity Studies)

**Reproductive toxicity:**

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Test type	Route of application	Species	Method
Propan-2-ol 67-63-0	NOAEL P 853 mg/kg	One generation study	oral: drinking water	rat	equivalent or similar to OECD Guideline 415 (One-Generation Reproduction Toxicity Study)
Propan-2-ol 67-63-0	NOAEL P 500 mg/kg NOAEL F1 1.000 mg/kg	Two generation study	oral: gavage	rat	equivalent or similar to OECD Guideline 416 (Two-Generation Reproduction Toxicity Study)

**STOT-single exposure:**

No data available.

**STOT-repeated exposure:**

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Route of application	Exposure time / Frequency of treatment	Species	Method
acetone 67-64-1	NOAEL 900 mg/kg	oral: drinking water	13 w daily	rat	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
Propan-2-ol 67-63-0		inhalation: vapour	104 w 6 h/d, 5 d/w	rat	OECD Guideline 451 (Carcinogenicity Studies)
benzothiazole-2-thiol 149-30-4	NOAEL 375 mg/kg	oral: gavage	13 weeks 5 days/week	rat	not specified

**Aspiration hazard:**

The mixture is classified based on Viscosity data.

Hazardous substances CAS-No.	Viscosity (kinematic) Value	Temperature	Method	Remarks
Propan-2-ol 67-63-0	1,8 mm <sup>2</sup> /s	40 °C	ASTM Standard D7042	

**11.2 Information on other hazards**

not applicable

**SECTION 12: Ecological information****General ecological information:**

Do not empty into drains / surface water / ground water.

**12.1. Toxicity****Toxicity (Fish):**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
acetone 67-64-1	LC50	8.120 mg/l	96 h	Pimephales promelas	OECD Guideline 203 (Fish, Acute Toxicity Test)
Propan-2-ol 67-63-0	LC50	> 9.640 - 10.000 mg/l	96 h	Pimephales promelas	OECD Guideline 203 (Fish, Acute Toxicity Test)
Diethylol-p-toluidine 3077-12-1	LC50	> 100 mg/l	96 h	Cyprinus carpio	OECD Guideline 203 (Fish, Acute Toxicity Test)
benzothiazole-2-thiol 149-30-4	LC50	0,73 mg/l	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)
benzothiazole-2-thiol 149-30-4	NOEC	0,041 mg/l	89 d	Oncorhynchus mykiss	other guideline:

**Toxicity (aquatic invertebrates):**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
acetone 67-64-1	EC50	8.800 mg/l	48 h	Daphnia pulex	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Diethylol-p-toluidine 3077-12-1	EC50	48 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
benzothiazole-2-thiol 149-30-4	EC50	0,71 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)

**Chronic toxicity (aquatic invertebrates):**

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
acetone 67-64-1	NOEC	2.212 mg/l	28 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)
Propan-2-ol 67-63-0	NOEC	30 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)
benzothiazole-2-thiol 149-30-4	NOEC	0,08 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)

**Toxicity (Algae):**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
acetone 67-64-1	NOEC	530 mg/l	8 d	Microcystis aeruginosa	DIN 38412-09
Propan-2-ol 67-63-0	EC50	> 1.000 mg/l	96 h	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)	OECD Guideline 201 (Alga, Growth Inhibition Test)
Propan-2-ol 67-63-0	NOEC	1.000 mg/l	96 h	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)	OECD Guideline 201 (Alga, Growth Inhibition Test)
Diethylol-p-toluidine 3077-12-1	EC50	> 100 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Diethylol-p-toluidine 3077-12-1	NOEC	100 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
benzothiazole-2-thiol 149-30-4	EC50	0,5 mg/l	72 h	Pseudokirchneriella subcapitata (reported as Raphidocelis subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
benzothiazole-2-thiol 149-30-4	NOEC	0,066 mg/l	72 h	Pseudokirchneriella subcapitata (reported as Raphidocelis subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)

#### Toxicity (microorganisms):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
acetone 67-64-1	EC10	1.000 mg/l	30 min	Pseudomonas putida	DIN 38412, part 27 (Bacterial oxygen consumption test)
Propan-2-ol 67-63-0	EC50	> 1.000 mg/l	3 h	activated sludge	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
Diethylol-p-toluidine 3077-12-1	EC50	> 1.000 mg/l	3 h	activated sludge of a predominantly domestic sewage	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
benzothiazole-2-thiol 149-30-4	EC50	3.301 mg/l	3 h	activated sludge	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)

#### 12.2. Persistence and degradability

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Test type	Degradability	Exposure time	Method
acetone 67-64-1	readily biodegradable	aerobic	81 - 92 %	30 d	EU Method C.4-E (Determination of the "Ready" Biodegradability Closed Bottle Test)
Propan-2-ol 67-63-0	readily biodegradable	aerobic	70 - 84 %	30 d	EU Method C.4-E (Determination of the "Ready" Biodegradability Closed Bottle Test)
Diethylol-p-toluidine 3077-12-1	not readily biodegradable.	aerobic	1,5 %	29 d	OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test)
benzothiazole-2-thiol 149-30-4		aerobic	2,5 %	14 d	OECD Guideline 301 C (Ready Biodegradability: Modified MITI Test (I))

#### 12.3. Bioaccumulative potential

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Bioconcentration factor (BCF)	Exposure time	Temperature	Species	Method
benzothiazole-2-thiol 149-30-4	< 8	6 Weeks		Cyprinus carpio	other guideline:

#### 12.4. Mobility in soil

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	LogPow	Temperature	Method
acetone 67-64-1	-0,24		OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)
Propan-2-ol 67-63-0	0,05		OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)
Diethylol-p-toluidine 3077-12-1	2	35 °C	OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC Method)
benzothiazole-2-thiol 149-30-4	2,34 - 2,5		not specified

#### 12.5. Results of PBT and vPvB assessment

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	PBT / vPvB
acetone 67-64-1	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Propan-2-ol 67-63-0	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Diethylol-p-toluidine 3077-12-1	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
benzothiazole-2-thiol 149-30-4	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

#### 12.6. Endocrine disrupting properties

not applicable

#### 12.7. Other adverse effects

No data available.

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

Product disposal:

Do not empty into drains / surface water / ground water.

Dispose of in accordance with local and national regulations.

Disposal of uncleaned packages:

Disposal must be made according to official regulations.

After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.

Waste code

14 06 03 Other solvents and solvent mixtures

The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We will be happy to advise you.

**SECTION 14: Transport information****14.1. UN number or ID number**

ADR	1993
RID	1993
ADN	1993
IMDG	1993
IATA	1993

**14.2. UN proper shipping name**

ADR	FLAMMABLE LIQUID, N.O.S. (Acetone,Isopropanol)
RID	FLAMMABLE LIQUID, N.O.S. (Acetone,Isopropanol)
ADN	FLAMMABLE LIQUID, N.O.S. (Acetone,Isopropanol)
IMDG	FLAMMABLE LIQUID, N.O.S. (Acetone,Isopropanol)
IATA	Flammable liquid, n.o.s. (Acetone,Isopropanol)

**14.3. Transport hazard class(es)**

ADR	3
RID	3
ADN	3
IMDG	3
IATA	3

**14.4. Packing group**

ADR	II
RID	II
ADN	II
IMDG	II
IATA	II

**14.5. Environmental hazards**

ADR	not applicable
RID	not applicable
ADN	not applicable
IMDG	not applicable
IATA	not applicable

**14.6. Special precautions for user**

ADR	Special provision 640D Tunnelcode: (D/E)
RID	Special provision 640D
ADN	Special provision 640D
IMDG	not applicable
IATA	not applicable

**14.7. Maritime transport in bulk according to IMO instruments**

not applicable

**SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

Ozone Depleting Substance (ODS) (Regulation (EC) No 1005/2009):	Not applicable
Prior Informed Consent (PIC) (Regulation (EU) No 649/2012):	Not applicable
Persistent organic pollutants (Regulation (EU) 2019/1021):	Not applicable



VOC content 98,5 %  
(2010/75/EC)

This product is regulated by Regulation (EU) 2019/1148: all suspicious transactions, and significant disappearances and thefts should be reported to the relevant national contact point. Please see [https://ec.europa.eu/home-affairs/what-we-do/policies/counter-terrorism/protection/implementation-explosives-precursors-legislation\\_en](https://ec.europa.eu/home-affairs/what-we-do/policies/counter-terrorism/protection/implementation-explosives-precursors-legislation_en).

#### **15.2. Chemical safety assessment**

A chemical safety assessment has been carried out.

#### **National regulations/information (Germany):**

WGK: WGK 1: slightly hazardous to water (Ordinance on facilities for handling substances that are hazardous to water (AwSV) )  
Classification according to AwSV, Annex 1 (5.2)

Storage class according to TRGS 510: 3

## SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows:

H225 Highly flammable liquid and vapour.  
H302 Harmful if swallowed.  
H317 May cause an allergic skin reaction.  
H318 Causes serious eye damage.  
H319 Causes serious eye irritation.  
H336 May cause drowsiness or dizziness.  
H400 Very toxic to aquatic life.  
H410 Very toxic to aquatic life with long lasting effects.  
H412 Harmful to aquatic life with long lasting effects.

ED:	Substance identified as having endocrine disrupting properties
EU OEL:	Substance with a Union workplace exposure limit
EU EXPLD 1:	Substance listed in Annex I, Reg (EC) No. 2019/1148
EU EXPLD 2	Substance listed in Annex II, Reg (EC) No. 2019/1148
SVHC:	Substance of very high concern (REACH Candidate List)
PBT:	Substance fulfilling persistent, bioaccumulative and toxic criteria
PBT/vPvB:	Substance fulfilling persistent, bioaccumulative and toxic plus very persistent and very bioaccumulative criteria
vPvB:	Substance fulfilling very persistent and very bioaccumulative criteria

### Further information:

This Safety Data Sheet has been produced for sales from Henkel to parties purchasing from Henkel, is based on Regulation (EC) No 1907/2006 and provides information in accordance with applicable regulations of the European Union only. In that respect, no statement, warranty or representation of any kind is given as to compliance with any statutory laws or regulations of any other jurisdiction or territory other than the European Union. When exporting to territories other than the European Union, please consult with the respective Safety Data Sheet of the concerned territory to ensure compliance or liaise with Henkel's Product Safety and Regulatory Affairs Department (SDSinfo.Adhesive@henkel.com) prior to export to other territories than the European Union.

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Dear Customer,

Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your\_company.com).

**Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.**