



Safety Data Sheet according to (EC) No 1907/2006 as amended

Page 1 of 19

LOCTITE SI 5366 CL CR310ML EGFD

SDS No. : 164436
V004.0

Revision: 07.01.2025

printing date: 22.04.2025

Replaces version from: 06.04.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

LOCTITE SI 5366 CL CR310ML EGFD
UFI: Y3GH-T0GW-E00K-HKY5

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:
Silicone sealant

1.3. Details of the supplier of the safety data sheet

Henkel AG & Co. KGaA
Henkelstr. 67
40589 Düsseldorf

Germany

Phone: +49 211 797 0

SDSinfo.Adhesive@henkel.com

For Safety Data Sheet updates please visit our website www.mysds.henkel.com or www.henkel-adhesives.com.

1.4. Emergency telephone number

The Henkel information service also provides an around-the-clock telephone service on phone no.+49-(0)211-797-3350 for exceptional cases.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (CLP):

| | |
|-------------------------------------|------------|
| Skin irritation | Category 2 |
| H315 Causes skin irritation. | |
| Serious eye irritation | Category 2 |
| H319 Causes serious eye irritation. | |

2.2. Label elements

Label elements (CLP):

Hazard pictogram:



Signal word:

Warning

| | |
|--|--|
| Hazard statement: | H315 Causes skin irritation. H319 Causes serious eye irritation. |
| Precautionary statement: Response | P337+P313 If eye irritation persists: Get medical advice/attention. P302+P352 IF ON SKIN: Wash with plenty of soap and water. |

2.3. Other hazards

None if used properly.
Self-classification according to Article 12(b) of (EU) 1272/2008.

Following substances are present in a concentration \geq the concentration limit for depiction in Section 3 and fulfill the criteria for PBT/vPvB, or were identified as endocrine disruptor (ED):

| | |
|---|----------|
| octamethylcyclotetrasiloxane 556-67-2 | PBT/vPvB |
| Decamethylcyclopentasiloxane 541-02-6 | PBT/vPvB |
| Dodecamethylcyclohexasiloxane 540-97-6 | PBT/vPvB |

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Declaration of the ingredients according to CLP (EC) No 1272/2008:

| Hazardous components CAS-No. EC Number REACH-Reg No. | Concentration | Classification | Specific Conc. Limits, M-factors and ATEs | Add. Information |
|--|---------------|---|---|------------------|
| Methyltriacetoxysilane 4253-34-3 224-221-9 01-2119962266-32 01-2119987097-22 | 1- < 3 % | Skin Corr. 1C, H314 Eye Dam. 1, H318 Acute Tox. 4, Oral, H302 | | |
| octamethylcyclotetrasiloxane 556-67-2 209-136-7 01-2119529238-36 | 0,25- < 2,5 % | Aquatic Chronic 1, H410 Repr. 2, H361f Flam. Liq. 3, H226 | M chronic = 10 | SVHC PBT/vPvB |
| Decamethylcyclopentasiloxane 541-02-6 208-764-9 01-2119511367-43 | 0,1- < 1 % | | | SVHC PBT/vPvB |
| Dodecamethylcyclohexasiloxane 540-97-6 208-762-8 01-2119517435-42 | 0,1- < 1 % | | | SVHC PBT/vPvB |

**If no ATE values are displayed, please refer to LD/LC50 values in Section 11.
For full text of the H - statements and other abbreviations see section 16 "Other information".**

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:
Move to fresh air. If symptoms persist, seek medical advice.

Skin contact:
Rinse with running water and soap.
Obtain medical attention if irritation persists.

Eye contact:
Rinse immediately with plenty of running water (for 10 minutes), seek medical attention from a specialist.

Ingestion:
Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

SKIN: Redness, inflammation.

EYE: Irritation, conjunctivitis.

4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

water, carbon dioxide, foam, powder

Extinguishing media which must not be used for safety reasons:

High pressure waterjet

5.2. Special hazards arising from the substance or mixture

In the event of a fire, carbon monoxide (CO), carbon dioxide (CO₂) and nitrogen oxides (NO_x) can be released.

Silicon dioxide

5.3. Advice for firefighters

Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

Additional information:

In case of fire, keep containers cool with water spray.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Avoid contact with skin and eyes.

Wear protective equipment.

Ensure adequate ventilation.

6.2. Environmental precautions

Do not empty into drains / surface water / ground water.

6.3. Methods and material for containment and cleaning up

Dispose of contaminated material as waste according to Section 13.

For small spills wipe up with paper towel and place in container for disposal.

For large spills absorb onto inert absorbent material and place in sealed container for disposal.

6.4. Reference to other sections

See advice in section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid skin and eye contact.

See advice in section 8

Hygiene measures:

Wash hands before work breaks and after finishing work.

Do not eat, drink or smoke while working.

Good industrial hygiene practices should be observed.

7.2. Conditions for safe storage, including any incompatibilities

Store in a cool, well-ventilated place.

Refer to Technical Data Sheet.

Never allow product to get in contact with water during storage

7.3. Specific end use(s)

Silicone sealant

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational Exposure Limits

Valid for
Germany

None

Predicted No-Effect Concentration (PNEC):

| Name on list | Environmental Compartment | Exposure period | Value | | | | Remarks |
|---|------------------------------|-----------------|--------------|-----|------------|--------|----------------------------------|
| | | | mg/l | ppm | mg/kg | others | |
| Methylsilanetriyl triacetate 4253-34-3 | sewage treatment plant (STP) | | 6,9 mg/l | | | | |
| Methylsilanetriyl triacetate 4253-34-3 | sediment (freshwater) | | | | 4,8 mg/kg | | |
| Methylsilanetriyl triacetate 4253-34-3 | sediment (marine water) | | | | 0,48 mg/kg | | |
| Methylsilanetriyl triacetate 4253-34-3 | Soil | | | | 0,19 mg/kg | | |
| Methylsilanetriyl triacetate 4253-34-3 | Predator | | | | | | no potential for bioaccumulation |
| Octamethylcyclotetrasiloxane 556-67-2 | aqua (freshwater) | | 0,0015 mg/l | | | | |
| Octamethylcyclotetrasiloxane 556-67-2 | aqua (marine water) | | 0,00015 mg/l | | | | |
| Octamethylcyclotetrasiloxane 556-67-2 | sewage treatment plant (STP) | | 10 mg/l | | | | |
| Octamethylcyclotetrasiloxane 556-67-2 | sediment (freshwater) | | | | 3 mg/kg | | |
| Octamethylcyclotetrasiloxane 556-67-2 | sediment (marine water) | | | | 0,3 mg/kg | | |
| Octamethylcyclotetrasiloxane 556-67-2 | oral | | | | 41 mg/kg | | |
| Octamethylcyclotetrasiloxane 556-67-2 | Soil | | | | 0,84 mg/kg | | |
| Decamethylcyclopentasiloxane 541-02-6 | aqua (freshwater) | | 0,0012 mg/l | | | | |
| Decamethylcyclopentasiloxane 541-02-6 | aqua (marine water) | | 0,00012 mg/l | | | | |
| Decamethylcyclopentasiloxane 541-02-6 | sewage treatment plant (STP) | | 10 mg/l | | | | |
| Decamethylcyclopentasiloxane 541-02-6 | sediment (freshwater) | | | | 11 mg/kg | | |
| Decamethylcyclopentasiloxane 541-02-6 | Soil | | | | 2,54 mg/kg | | |
| Decamethylcyclopentasiloxane 541-02-6 | oral | | | | 16 mg/kg | | |
| Decamethylcyclopentasiloxane 541-02-6 | sediment (marine water) | | | | 1,1 mg/kg | | |
| Dodecamethylcyclohexasiloxane 540-97-6 | sediment (freshwater) | | | | 13,5 mg/kg | | |
| Dodecamethylcyclohexasiloxane 540-97-6 | oral | | | | 66,7 mg/kg | | |
| Dodecamethylcyclohexasiloxane 540-97-6 | sediment (marine water) | | | | 1,35 mg/kg | | |

Derived No-Effect Level (DNEL):

| Name on list | Application Area | Route of Exposure | Health Effect | Exposure Time | Value | Remarks |
|---|--------------------|-------------------|--|---------------|------------|----------------------------------|
| Methylsilanetriyl triacetate 4253-34-3 | Workers | inhalation | Long term exposure - systemic effects | | 25 mg/m3 | no potential for bioaccumulation |
| Methylsilanetriyl triacetate 4253-34-3 | Workers | inhalation | Acute/short term exposure - systemic effects | | 25 mg/m3 | no potential for bioaccumulation |
| Methylsilanetriyl triacetate 4253-34-3 | Workers | dermal | Long term exposure - systemic effects | | 14,5 mg/kg | no potential for bioaccumulation |
| Methylsilanetriyl triacetate 4253-34-3 | Workers | dermal | Acute/short term exposure - systemic effects | | 14,5 mg/kg | no potential for bioaccumulation |
| Methylsilanetriyl triacetate 4253-34-3 | General population | inhalation | Long term exposure - local effects | | 5,1 mg/m3 | no potential for bioaccumulation |
| Methylsilanetriyl triacetate 4253-34-3 | General population | inhalation | Acute/short term exposure - local effects | | 5,1 mg/m3 | no potential for bioaccumulation |
| Methylsilanetriyl triacetate 4253-34-3 | General population | dermal | Long term exposure - systemic effects | | 7,2 mg/kg | no potential for bioaccumulation |
| Methylsilanetriyl triacetate 4253-34-3 | General population | dermal | Acute/short term exposure - systemic effects | | 7,2 mg/kg | no potential for bioaccumulation |
| Methylsilanetriyl triacetate 4253-34-3 | General population | oral | Long term exposure - systemic effects | | 1 mg/kg | no potential for bioaccumulation |
| Methylsilanetriyl triacetate 4253-34-3 | General population | oral | Acute/short term exposure - systemic effects | | 1 mg/kg | no potential for bioaccumulation |
| Octamethylcyclotetrasiloxane 556-67-2 | Workers | inhalation | Long term exposure - systemic effects | | 73 mg/m3 | |
| Octamethylcyclotetrasiloxane 556-67-2 | Workers | inhalation | Long term exposure - local effects | | 73 mg/m3 | |
| Octamethylcyclotetrasiloxane 556-67-2 | General population | inhalation | Long term exposure - systemic effects | | 13 mg/m3 | |
| Octamethylcyclotetrasiloxane 556-67-2 | General population | inhalation | Long term exposure - local effects | | 13 mg/m3 | |
| Octamethylcyclotetrasiloxane 556-67-2 | General population | oral | Long term exposure - systemic effects | | 3,7 mg/kg | |
| Decamethylcyclopentasiloxane 541-02-6 | Workers | inhalation | Long term exposure - systemic effects | | 97,3 mg/m3 | |
| Decamethylcyclopentasiloxane 541-02-6 | Workers | inhalation | Long term exposure - local effects | | 24,2 mg/m3 | |
| Decamethylcyclopentasiloxane 541-02-6 | General population | oral | Long term exposure - systemic effects | | 5 mg/kg | |
| Decamethylcyclopentasiloxane 541-02-6 | General population | inhalation | Long term exposure - systemic effects | | 17,3 mg/m3 | |
| Decamethylcyclopentasiloxane 541-02-6 | General population | inhalation | Long term exposure - local effects | | 4,3 mg/m3 | |

Biological Exposure Indices:

None

8.2. Exposure controls:

Engineering controls:

Ensure good ventilation/extraction.

Respiratory protection:

Ensure adequate ventilation.

An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area

Filter type: A (EN 14387)

Hand protection:

Chemical-resistant protective gloves (EN 374).

Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):

nitrile rubber (NBR; \geq 0.4 mm thickness)

Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):

nitrile rubber (NBR; \geq 0.4 mm thickness)

This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:

Safety glasses with sideshields or chemical safety goggles should be worn if there is a risk of splashing.

Protective eye equipment should conform to EN166.

Skin protection:

Wear suitable protective clothing.

Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Advices to personal protection equipment:

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions.

Personal protective equipment should conform to the relevant EN standard.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| | |
|---|---|
| Delivery form | paste |
| Colour | Clear |
| Odor | Acetic acid |
| Physical state | liquid |
| Melting point | Not applicable, Product is a liquid |
| Solidification temperature | < -50 °C (< -58 °F) |
| Initial boiling point | > 100 °C (> 212 °F) |
| Flammability | The product is not flammable. |
| Explosive limits | Not applicable, The product is not flammable. |
| Flash point | > 150 °C (> 302 °F) |
| Auto-ignition temperature | Not applicable, The product is not flammable. |
| Decomposition temperature | Not applicable, Substance/mixture is not self-reactive, no organic peroxide and does not decompose under foreseen conditions of use |
| pH | Not applicable, Product is non-soluble (in water). |
| Viscosity (kinematic) (40 °C (104 °F);) | > 20,5 mm ² /s |
| Solubility (qualitative) (20 °C (68 °F); Solvent: Water) | Partially soluble |
| Solubility (qualitative) | Insoluble |

| | |
|--|---------------------------------------|
| (Solvent: Acetone) | |
| Partition coefficient: n-octanol/water | Not applicable |
| Vapour pressure (20 °C (68 °F)) | Mixture < 0,1 mm hg |
| Density (20 °C (68 °F)) | 1,04 g/cm ³ None |
| Relative vapour density: (20 °C) | > 1 |
| Particle characteristics | Not applicable Product is a liquid |

9.2. Other information

Other information not applicable for this product

SECTION 10: Stability and reactivity

10.1. Reactivity

Reacts with oxidants, acids and lyes

10.2. Chemical stability

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

See section reactivity

10.4. Conditions to avoid

Stable under normal conditions of storage and use.
Excessive heat.

10.5. Incompatible materials

See section reactivity.

10.6. Hazardous decomposition products

None if used for intended purpose.

SECTION 11: Toxicological information**General toxicological information:**

Acetic acid is liberated slowly upon contact with moisture.

Acetic acid released during polymerisation of acetoxy curing RTV silicones is irritating to the eyes

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**Acute oral toxicity:**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Value type | Value | Species | Method |
|---|---------------|---------------|---------|---|
| Methyltriacetoxysilane 4253-34-3 | LD50 | 1.600 mg/kg | rat | OECD Guideline 401 (Acute Oral Toxicity) |
| octamethylcyclotetrasiloxane 556-67-2 | LD50 | > 4.800 mg/kg | rat | equivalent or similar to OECD Guideline 401 (Acute Oral Toxicity) |
| Decamethylcyclopentasiloxane 541-02-6 | LD50 | > 5.000 mg/kg | rat | equivalent or similar to OECD Guideline 401 (Acute Oral Toxicity) |
| Dodecamethylcyclohexasiloxane 540-97-6 | LD50 | > 2.000 mg/kg | rat | OECD Guideline 423 (Acute Oral toxicity) |

Acute dermal toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Value type | Value | Species | Method |
|---|---------------|---------------|---------|---|
| octamethylcyclotetrasiloxane 556-67-2 | LD50 | > 2.375 mg/kg | rat | equivalent or similar to OECD Guideline 402 (Acute Dermal Toxicity) |
| Decamethylcyclopentasiloxane 541-02-6 | LD50 | > 2.000 mg/kg | rabbit | equivalent or similar to OECD Guideline 402 (Acute Dermal Toxicity) |
| Dodecamethylcyclohexasiloxane 540-97-6 | LD50 | > 2.000 mg/kg | rat | OECD Guideline 402 (Acute Dermal Toxicity) |

Acute inhalative toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Value type | Value | Test atmosphere | Exposure time | Species | Method |
|--|------------|-----------|-----------------|---------------|---------|--|
| octamethylcyclotetrasiloxane 556-67-2 | LC50 | 36 mg/l | dust/mist | 4 h | rat | OECD Guideline 403 (Acute Inhalation Toxicity) |
| Decamethylcyclopentasiloxane 541-02-6 | LC50 | 8,67 mg/l | dust/mist | 4 h | rat | OECD Guideline 403 (Acute Inhalation Toxicity) |

Skin corrosion/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Result | Exposure time | Species | Method |
|---|----------------|---------------|---------|---|
| Methyltriacetoxysilane 4253-34-3 | corrosive | 4 h | rabbit | OECD Guideline 404 (Acute Dermal Irritation / Corrosion) |
| octamethylcyclotetrasiloxane 556-67-2 | not irritating | | rabbit | equivalent or similar to OECD Guideline 404 (Acute Dermal Irritation / Corrosion) |
| Decamethylcyclopentasiloxane 541-02-6 | not irritating | 24 h | rabbit | equivalent or similar to OECD Guideline 404 (Acute Dermal Irritation / Corrosion) |
| Dodecamethylcyclohexasiloxane 540-97-6 | not irritating | 4 h | rabbit | OECD Guideline 404 (Acute Dermal Irritation / Corrosion) |

Serious eye damage/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Result | Exposure time | Species | Method |
|---|--|---------------|---------|--|
| Methyltriacetoxysilane 4253-34-3 | Category 1 (irreversible effects on the eye) | | rabbit | OECD Guideline 405 (Acute Eye Irritation / Corrosion) |
| octamethylcyclotetrasiloxane 556-67-2 | not irritating | | rabbit | equivalent or similar to OECD Guideline 405 (Acute Eye Irritation / Corrosion) |
| Decamethylcyclopentasiloxane 541-02-6 | not irritating | | rabbit | equivalent or similar to OECD Guideline 405 (Acute Eye Irritation / Corrosion) |
| Dodecamethylcyclohexasiloxane 540-97-6 | not irritating | | rabbit | OECD Guideline 405 (Acute Eye Irritation / Corrosion) |

Respiratory or skin sensitization:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Result | Test type | Species | Method |
|---|-----------------|------------------------------------|------------|--|
| Methyltriacetoxysilane 4253-34-3 | not sensitising | Guinea pig maximisation test | guinea pig | OECD Guideline 406 (Skin Sensitisation) |
| octamethylcyclotetrasiloxane 556-67-2 | not sensitising | Guinea pig maximisation test | guinea pig | OECD Guideline 406 (Skin Sensitisation) |
| Decamethylcyclopentasiloxane 541-02-6 | not sensitising | Mouse local lymphnode assay (LLNA) | mouse | equivalent or similar to OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay) |
| Dodecamethylcyclohexasiloxane 540-97-6 | not sensitising | Guinea pig maximisation test | guinea pig | OECD Guideline 406 (Skin Sensitisation) |

Germ cell mutagenicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Result | Type of study / Route of administration | Metabolic activation / Exposure time | Species | Method |
|---|----------|--|--------------------------------------|---------|--|
| Methyltriacetoxysilane 4253-34-3 | negative | bacterial reverse mutation assay (e.g Ames test) | with and without | | OECD Guideline 471 (Bacterial Reverse Mutation Assay) |
| Methyltriacetoxysilane 4253-34-3 | negative | in vitro mammalian chromosome aberration test | with and without | | OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test) |
| Methyltriacetoxysilane 4253-34-3 | negative | mammalian cell gene mutation assay | with and without | | OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test) |
| octamethylcyclotetrasiloxane 556-67-2 | negative | bacterial gene mutation assay | with and without | | OECD Guideline 471 (Bacterial Reverse Mutation Assay) |
| octamethylcyclotetrasiloxane 556-67-2 | negative | in vitro mammalian chromosome aberration test | with and without | | equivalent or similar to OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test) |
| octamethylcyclotetrasiloxane 556-67-2 | negative | mammalian cell gene mutation assay | with and without | | equivalent or similar to OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test) |
| Decamethylcyclopentasiloxane 541-02-6 | negative | bacterial reverse mutation assay (e.g Ames test) | with and without | | OECD Guideline 471 (Bacterial Reverse Mutation Assay) |
| Decamethylcyclopentasiloxane 541-02-6 | negative | in vitro mammalian chromosome aberration test | with and without | | OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test) |
| Decamethylcyclopentasiloxane 541-02-6 | negative | mammalian cell gene mutation assay | with and without | | equivalent or similar to OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test) |
| Dodecamethylcyclohexasiloxane 540-97-6 | negative | bacterial reverse mutation assay (e.g Ames test) | with and without | | OECD Guideline 471 (Bacterial Reverse Mutation Assay) |
| Dodecamethylcyclohexasiloxane 540-97-6 | negative | mammalian cell gene mutation assay | with and without | | OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test) |
| octamethylcyclotetrasiloxane 556-67-2 | negative | inhalation | | rat | equivalent or similar to OECD Guideline 475 (Mammalian Bone Marrow Chromosome Aberration Test) |
| octamethylcyclotetrasiloxane 556-67-2 | negative | oral: gavage | | rat | equivalent or similar to OECD Guideline 478 (Genetic Toxicology: Rodent Dominant Lethal Test) |
| Decamethylcyclopentasiloxane 541-02-6 | negative | inhalation | | rat | OECD Guideline 486 (Unscheduled DNA Synthesis (UDS) Test with Mammalian Liver Cells in vivo) |
| Decamethylcyclopentasiloxane 541-02-6 | negative | inhalation: vapour | | rat | OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test) |
| Dodecamethylcyclohexasiloxane 540-97-6 | negative | intraperitoneal | | mouse | OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test) |

Carcinogenicity

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

| Hazardous components CAS-No. | Result | Route of application | Exposure time / Frequency of treatment | Species | Sex | Method |
|--|------------------|-------------------------|---|---------|-------------|---|
| Decamethylcyclopentasiloxane 541-02-6 | not carcinogenic | inhalation: vapour | 2 y 6 h/d, 5 d/w | rat | male/female | EPA OPPTS 870.4300 (Combined Chronic Toxicity / Carcinogenicity) |

Reproductive toxicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Result / Value | Test type | Route of application | Species | Method |
|---|---|-----------------------------|-------------------------|---------|---|
| Methyltriacetoxysilane 4253-34-3 | NOAEL P \geq 1.000 mg/kg NOAEL F1 \geq 1.000 mg/kg | screening | oral: gavage | rat | OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test) |
| octamethylcyclotetrasiloxane 556-67-2 | NOAEL P 300 ppm NOAEL F1 300 ppm | two- generation study | inhalation | rat | equivalent or similar to OECD Guideline 416 (Two- Generation Reproduction Toxicity Study) |
| Decamethylcyclopentasiloxane 541-02-6 | NOAEL P \geq 2,496 mg/l NOAEL F1 \geq 2,496 mg/l NOAEL F2 \geq 2,496 mg/l | two- generation study | inhalation: vapour | rat | EPA OPPTS 870.3800 (Reproduction and Fertility Effects) |
| Dodecamethylcyclohexasiloxane 540-97-6 | NOAEL P 1.000 mg/kg NOAEL F1 1.000 mg/kg | screening | oral: gavage | rat | OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test) |

STOT-single exposure:

No data available.

STOT-repeated exposure:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Result / Value | Route of application | Exposure time / Frequency of treatment | Species | Method |
|---|----------------------|-----------------------|---|---------|---|
| Methyltriacetoxysilane 4253-34-3 | NOAEL 50 mg/kg | oral: gavage | 28-51 d daily | rat | OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test) |
| octamethylcyclotetrasiloxane 556-67-2 | LOAEL 35 ppm | inhalation | 6 h nose only inhalation 5 days/week for 13 weeks | rat | OECD Guideline 412 (Repeated Dose Inhalation Toxicity: 28/14-Day) |
| octamethylcyclotetrasiloxane 556-67-2 | NOAEL 960 mg/kg | dermal | 3 w 5 d/w | rabbit | equivalent or similar to OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study) |
| Decamethylcyclopentasiloxane 541-02-6 | NOAEL >= 1.000 mg/kg | oral: gavage | 13 w daily | rat | OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents) |
| Decamethylcyclopentasiloxane 541-02-6 | NOAEL >= 2,42 mg/l | inhalation: vapour | 2 y 6 h/d, 5 d/w | rat | equivalent or similar to OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies) |
| Decamethylcyclopentasiloxane 541-02-6 | NOAEL >= 1.600 mg/kg | oral: gavage | 28 d 6 h/d, 7 d/w | rat | equivalent or similar to OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study) |
| Dodecamethylcyclohexasiloxane 540-97-6 | NOAEL 1.000 mg/kg | oral: gavage | 29 d daily, 7 d/w | rat | OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test) |

Aspiration hazard:

No data available.

11.2 Information on other hazards

not applicable

SECTION 12: Ecological information**General ecological information:**

Do not empty into drains / surface water / ground water.

Self-classification according to Article 12(b) of (EU) 1272/2008.

12.1. Toxicity**Toxicity (Fish):**

LC50 (fish) > 100 mg/l (expert judgement)

NOEC (fish) > 1 mg/l (expert judgement)

The table below presents the data of the classified substances present in the mixture.

| Hazardous substances CAS-No. | Value type | Value | Exposure time | Species | Method |
|---|---------------|-----------------------------|---------------|--|--|
| Methyltriacetoxysilane 4253-34-3 | LC50 | > 110 mg/l | 96 h | Oncorhynchus mykiss | OECD Guideline 203 (Fish, Acute Toxicity Test) |
| octamethylcyclotetrasiloxane 556-67-2 | NOEC | 0,0044 mg/l | 93 d | Salmo gairdneri (new name: Oncorhynchus mykiss) | EPA OPPTS 797.1600 (Fish Early Life Stage Toxicity Test) |
| octamethylcyclotetrasiloxane 556-67-2 | LC50 | Toxicity > Water solubility | 96 h | Oncorhynchus mykiss | EPA OTS 797.1400 (Fish Acute Toxicity Test) |
| Decamethylcyclopentasiloxane 541-02-6 | LC50 | Toxicity > Water solubility | 96 h | Leuciscus idus | OECD Guideline 204 (Fish, Prolonged Toxicity Test: 14-day Study) |
| Decamethylcyclopentasiloxane 541-02-6 | NOEC | Toxicity > Water solubility | 90 d | Oncorhynchus mykiss | OECD Guideline 210 (fish early life stage toxicity test) |
| Dodecamethylcyclohexasiloxane 540-97-6 | NOEC | Toxicity > Water solubility | 90 d | Oncorhynchus mykiss | OECD Guideline 210 (fish early life stage toxicity test) |

Toxicity (aquatic invertebrates):

EC50 (dafnia) >100 mg/l (OECD 211)

The table below presents the data of the classified substances present in the mixture.

| Hazardous substances CAS-No. | Value type | Value | Exposure time | Species | Method |
|--|---------------|-----------------------------|---------------|---------------|--|
| Methyltriacetoxysilane 4253-34-3 | EC50 | > 500 mg/l | 48 h | Daphnia magna | EU Method C.2 (Acute Toxicity for Daphnia) |
| octamethylcyclotetrasiloxane 556-67-2 | EC50 | Toxicity > Water solubility | 48 h | Daphnia magna | EPA OTS 797.1300 (Aquatic Invertebrate Acute Toxicity Test, Freshwater Daphnids) |
| Decamethylcyclopentasiloxane 541-02-6 | EC50 | Toxicity > Water solubility | 48 h | Daphnia magna | OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test) |

Chronic toxicity (aquatic invertebrates):

NOEC (dafnia) > 1 mg/l (OECD 211)

The table below presents the data of the classified substances present in the mixture.

| Hazardous substances CAS-No. | Value type | Value | Exposure time | Species | Method |
|--|---------------|-----------------------------|---------------|---------------|--|
| Methyltriacetoxysilane 4253-34-3 | NOEC | 100 mg/l | 21 d | Daphnia magna | OECD 211 (Daphnia magna, Reproduction Test) |
| octamethylcyclotetrasiloxane 556-67-2 | NOEC | 7.9 µg/l | 21 d | Daphnia magna | EPA OTS 797.1330 (Daphnid Chronic Toxicity Test) |
| Decamethylcyclopentasiloxane 541-02-6 | NOEC | Toxicity > Water solubility | 21 d | Daphnia magna | OECD 211 (Daphnia magna, Reproduction Test) |

| | | | | | |
|---|------|-----------------------------|------|---------------|---|
| Dodecamethylcyclohexasiloxane 540-97-6 | NOEC | Toxicity > Water solubility | 21 d | Daphnia magna | OECD 211 (Daphnia magna, Reproduction Test) |
|---|------|-----------------------------|------|---------------|---|

Toxicity (Algae):

NOEC (Algae) > 1 mg/l (OECD 201)

EC50 (Algae) > 100 mg/l (OECD 201)

The table below presents the data of the classified substances present in the mixture.

| Hazardous substances CAS-No. | Value type | Value | Exposure time | Species | Method |
|---|------------|-----------------------------|---------------|---|---|
| Methyltriacetoxysilane 4253-34-3 | EC50 | > 500 mg/l | 72 h | Raphidocelis subcapitata (new name: Pseudokirchneriella subcapitata) | EU Method C.3 (Algal Inhibition test) |
| Methyltriacetoxysilane 4253-34-3 | NOEC | 500 mg/l | 72 h | Raphidocelis subcapitata (new name: Pseudokirchneriella subcapitata) | EU Method C.3 (Algal Inhibition test) |
| octamethylcyclotetrasiloxane 556-67-2 | EC50 | Toxicity > Water solubility | 96 h | Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata) | EPA OTS 797.1050 (Algal Toxicity, Tiers I and II) |
| octamethylcyclotetrasiloxane 556-67-2 | EC10 | 0,022 mg/l | 96 h | Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata) | EPA OTS 797.1050 (Algal Toxicity, Tiers I and II) |
| Decamethylcyclopentasiloxane 541-02-6 | NOEC | Toxicity > Water solubility | 96 h | Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata) | OECD Guideline 201 (Algal Growth Inhibition Test) |
| Decamethylcyclopentasiloxane 541-02-6 | EC50 | Toxicity > Water solubility | 96 h | Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata) | OECD Guideline 201 (Algal Growth Inhibition Test) |
| Dodecamethylcyclohexasiloxane 540-97-6 | NOEC | Toxicity > Water solubility | 72 h | Pseudokirchneriella subcapitata | OECD Guideline 201 (Algal Growth Inhibition Test) |
| Dodecamethylcyclohexasiloxane 540-97-6 | EC50 | Toxicity > Water solubility | 72 h | Pseudokirchneriella subcapitata | OECD Guideline 201 (Algal Growth Inhibition Test) |

Toxicity (microorganisms):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

| Hazardous substances CAS-No. | Value type | Value | Exposure time | Species | Method |
|--|------------|-----------------------------|---------------|---|---|
| Methyltriacetoxysilane 4253-34-3 | EC10 | > 100 mg/l | 3 h | activated sludge of a predominantly domestic sewage | OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test) |
| octamethylcyclotetrasiloxane 556-67-2 | EC50 | Toxicity > Water solubility | 3 h | activated sludge | ISO 8192 (Test for Inhibition of Oxygen Consumption by Activated Sludge) |
| Decamethylcyclopentasiloxane 541-02-6 | EC50 | > 2.000 mg/l | 3 h | activated sludge, domestic | EU Method C.11 (Biodegradation: Activated Sludge Respiration Inhibition Test) |

12.2. Persistence and degradability

The table below presents the data of the classified substances present in the mixture.

| Hazardous substances CAS-No. | Result | Test type | Degradability | Exposure time | Method |
|---|----------------------------|-----------|---------------|------------------|--|
| Methyltriacetoxysilane 4253-34-3 | readily biodegradable | aerobic | 79,5 % | 28 d | OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test) |
| octamethylcyclotetrasiloxane 556-67-2 | not readily biodegradable. | aerobic | 3,7 % | 29 d | OECD Guideline 310 (Ready BiodegradabilityCO2 in Sealed Vessels (Headspace Test) |
| Decamethylcyclopentasiloxane 541-02-6 | not readily biodegradable. | aerobic | 0,14 % | 28 d | OECD Guideline 310 (Ready BiodegradabilityCO2 in Sealed Vessels (Headspace Test) |
| Dodecamethylcyclohexasiloxane 540-97-6 | not readily biodegradable. | aerobic | 4,47 % | 28 d | OECD Guideline 310 (Ready BiodegradabilityCO2 in Sealed Vessels (Headspace Test) |

12.3. Bioaccumulative potential

The table below presents the data of the classified substances present in the mixture.

| Hazardous substances CAS-No. | Bioconcentration factor (BCF) | Exposure time | Temperature | Species | Method |
|---|----------------------------------|---------------|-------------|------------------------|---|
| octamethylcyclotetrasiloxane 556-67-2 | 12.400 | 28 d | | Pimephales promelas | EPA OTS 797.1520 (Fish Bioconcentration Test-Rainbow Trout) |
| Decamethylcyclopentasiloxane 541-02-6 | 7.060 | 35 d | | Pimephales promelas | OECD Guideline 305 (Bioconcentration: Flow-through Fish Test) |
| Dodecamethylcyclohexasiloxane 540-97-6 | 1.160 | 49 d | | Pimephales promelas | OECD Guideline 305 (Bioconcentration: Flow-through Fish Test) |

12.4. Mobility in soil

The table below presents the data of the classified substances present in the mixture.

| Hazardous substances CAS-No. | LogPow | Temperature | Method |
|---|--------|-------------|---|
| Methyltriacetoxysilane 4253-34-3 | 0,25 | | QSAR (Quantitative Structure Activity Relationship) |
| octamethylcyclotetrasiloxane 556-67-2 | 6,98 | 21,7 °C | other guideline: |
| Decamethylcyclopentasiloxane 541-02-6 | 8,07 | 24,6 °C | other guideline: |
| Dodecamethylcyclohexasiloxane 540-97-6 | 8,87 | 23,6 °C | other guideline: |

12.5. Results of PBT and vPvB assessment

The table below presents the data of the classified substances present in the mixture.

| Hazardous substances CAS-No. | PBT / vPvB |
|---|---|
| Methyltriacetoxysilane 4253-34-3 | Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria. |
| octamethylcyclotetrasiloxane 556-67-2 | Fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria. |
| Decamethylcyclopentasiloxane 541-02-6 | Fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria. |
| Dodecamethylcyclohexasiloxane 540-97-6 | Fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria. |

12.6. Endocrine disrupting properties

not applicable

12.7. Other adverse effects

No data available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product disposal:

Do not empty into drains / surface water / ground water.

Dispose of in accordance with local and national regulations.

Disposal of uncleaned packages:

After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.

Waste code

08 04 09* waste adhesives and sealants containing organic solvents and other dangerous substances

The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We will be happy to advise you.

SECTION 14: Transport information

- 14.1. UN number or ID number**
Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.
- 14.2. UN proper shipping name**
Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.
- 14.3. Transport hazard class(es)**
Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.
- 14.4. Packing group**
Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.
- 14.5. Environmental hazards**
Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.
- 14.6. Special precautions for user**
Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.
- 14.7. Maritime transport in bulk according to IMO instruments**
not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

| | |
|--|----------------|
| Ozone Depleting Substance (ODS) (Regulation (EC) No 2024/590): | Not applicable |
| Prior Informed Consent (PIC) (Regulation (EU) No 649/2012): | Not applicable |
| Persistent organic pollutants (Regulation (EU) 2019/1021): | Not applicable |
| VOC content (2010/75/EC) | < 3 % |

National regulations/information (Germany):

| | |
|--------------------------------------|---|
| WGK: | WGK 3: highly hazardous to water (Ordinance on facilities for handling substances that are hazardous to water (AwSV)) Classification according to AwSV, Annex 1 (5.2) |
| Storage class according to TRGS 510: | 10 |

15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows:

H226 Flammable liquid and vapour.
H302 Harmful if swallowed.
H314 Causes severe skin burns and eye damage.
H318 Causes serious eye damage.
H361f Suspected of damaging fertility.
H410 Very toxic to aquatic life with long lasting effects.

| | |
|-------------|---|
| ED: | Substance identified as having endocrine disrupting properties |
| EU OEL: | Substance with a Union workplace exposure limit |
| EU EXPLD 1: | Substance listed in Annex I, Reg (EC) No. 2019/1148 |
| EU EXPLD 2: | Substance listed in Annex II, Reg (EC) No. 2019/1148 |
| SVHC: | Substance of very high concern (REACH Candidate List) |
| PBT: | Substance fulfilling persistent, bioaccumulative and toxic criteria |
| PBT/vPvB: | Substance fulfilling persistent, bioaccumulative and toxic plus very persistent and very bioaccumulative criteria |
| vPvB: | Substance fulfilling very persistent and very bioaccumulative criteria |

Further information:

This Safety Data Sheet has been produced for sales from Henkel to parties purchasing from Henkel, is based on Regulation (EC) No 1907/2006 and provides information in accordance with applicable regulations of the European Union only. In that respect, no statement, warranty or representation of any kind is given as to compliance with any statutory laws or regulations of any other jurisdiction or territory other than the European Union. When exporting to territories other than the European Union, please consult with the respective Safety Data Sheet of the concerned territory to ensure compliance or liaise with Henkel's Product Safety and Regulatory Affairs Department (SDSinfo.Adhesive@henkel.com) prior to export to other territories than the European Union.

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Dear Customer,
Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your_company.com).

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.